

BACKGROUND OF THE INVENTION

Japanese Patent Laid-Open No. No. 10-322391

discloses an example of the prior art internet service telephone communication connection method. In the disclosed communication terminal and communication method, when a calling terminal intends to make internet service communication, it sends out data including its own IP address in the internet service network via a separate line. A called terminal receiving the data including the IP address sent out from the calling terminal, connects itself to the internet service network, and the calling terminal also connects itself thereto. Thus, terminal-to-terminal communication is made possible.

1

In the above prior art example, the internet service providers, which the calling and called sides are subscribers of, are indefinite. Therefore, it is impossible to ensure a sufficient service quality.

5 In order to secure sufficient internet service
telephone communication quality, both the calling and
called sides may be interconnected via the same internet
service provider network. In this case, it is possible
to reduce the service quality deterioration due to
10 different internet service providers. However, where
each terminal as opposite side of communication is a
subscriber of a peculiar provider, it is necessary to
conclude contracts with a plurality of different
providers. Consequently, the contract expenditures are
15 increased. This is undesired from the standpoint of
reducing the internet service telephone communication
exepditures.

SUMMARY OF THE INVENTION

20 An object of the present invention is to provide
an internet service telephone set capable of providing
internet service telephone communication via the same
internet service provider network.

According to a first aspect of the present
invention, there is provided a telephone communication
25 system comprising a public network, an internet service
provider network and a plurality of telephone sets
accommodated in the public network, wherein when a
calling telephone set as an internet service provider

network subscriber provides connection point data for making internet service telephone communication to a called telephone set via a public network, the called telephone set receiving the connection point data

5 connects itself to an internet service provider network according to the connection point data, and then the calling telephone set connects itself to the internet service provider network.

According to a second aspect of the present
10 invention, there is provided a telephone communication system comprising a public network, an internet service provider network and a plurality of telephone sets accommodated in the public network, wherein when a calling telephone set as an internet service provider
15 network subscriber provides connection point data for making internet service telephone communication to a called telephone set via a public network, the called telephone set receiving the connection point data connects itself to an internet service provider network
20 according to the connection point data, and then the calling telephone set connects itself to the internet service provider network, the connection point data including at least an IP address in the internet service provider network and the telephone number of a point to
25 be connected to the internet service provider network.

According to a third aspect of the present invention, there is provided a telephone communication system comprising a public network, an internet service

provider network and a plurality of telephone sets accommodated in the public network, wherein when a calling telephone set as an internet service provider network subscriber provides connection point data for making internet service telephone communication to a called telephone set via a public network, the called telephone set receiving the connection point data connects itself to an internet service provider network according to the connection point data, and then the calling telephone set connects itself to the internet service provider network, the connection point data including at least an IP address in the internet service provider network and the telephone number of a point to be connected to the internet service provider network, a push-button telephone set having various function keys being provided between each of the plurality of telephone sets and the public network with a function of sending out a call from each telephone set.

The functions of each telephone set are executed on a personal computer. The functions of each telephone set are executed with an IVR (interactive voice response unit or a facsimile data server or a voice recognition dialer or a voice mail.

The telephone set comprises: a ten-key unit having dial keys and a function key for indicating an internet telephone service; a display unit for displaying a call arrival notification and results of various processes in the telephone set; an accumulating unit for storing

telephone number data and access identifier data of
internet connection points to be connected by the calling
and called sides; a voice codec to be started by a command
for voice communication in the internet; and a telephone
5 set control unit for detecting depressed push-buttons
in the ten-key unit, obtaining the connection point data
from the accumulating unit, sending out dial data and
connection point data via the public network, starting
the voice codec when the dialed side has been connected
10 to the internet service provider network and, upon
arrival of a call, retrieving for the connection point
data of the calling side, effecting connection of the
own side to the internet service provider network by
retrieving and referring to the accumulating unit
15 according to the connection point data and informing the
calling side of the connection.

Each telephone set further comprises an
enciphering unit for permitting exchange of connection
point data in terms of ciphers.

20 According to a fourth aspect of the present
invention, there is provided an internet communication
method comprising steps of: in response to provision,
by a calling telephone set as an internet service provider
network subscriber, of connection point data for making
25 internet service telephone communication to a called
telephone set via a public network, the called telephone
set receiving the connection point data connects itself
to an internet service provider network on the basis of

the connection point data, and then the calling telephone set connects itself to the internet service provider network.

5 ^{sub} ~~832~~ According to a fifth aspect of the present invention, there is provided an internet communication method comprising steps of: in response to provision, by a calling telephone set as an internet service provider network subscriber, of connection point data for making internet service telephone communication to a called
10 telephone set via a public network, the called telephone set receiving the connection point data connects itself to an internet service provider network on the basis of the connection point data, and then the calling telephone set connects itself to the internet service provider
15 network, the connection point data including at least an IP address in the internet service provider network and the telephone number of a point to be connected to the internet service provider network.

According to a sixth aspect of the present
20 invention, there is provided an internet communication method comprising steps of: in response to provision, by a calling telephone set as an internet service provider network subscriber, of connection point data for making internet service telephone communication to a called
25 telephone set via a public network, the called telephone set receiving the connection point data connects itself to an internet service provider network on the basis of the connection point data, and then the calling telephone

008090-48068560

set connects itself to the internet service provider network, the connection point data including at least an IP address in the internet service provider network and the telephone number of a point to be connected to the internet service provider network, a push-button telephone set having various function keys being provided between each of the plurality of telephone sets and the public network with a function of sending out a call from each telephone set.

10 In the present invention, in order to guarantee the service quality, an ablet (i.e., execution module having one time log-in identifier, pass word and dial-up and opposite side address data) is provided, which sends out, to the opposite side of communication, a means for
15 permitting the opposite side to call back in internet service telephone communication to the VPN (virtual private network) of its own subscribed provider.

According to the present invention, in addition to the feature of cheap communication fee of internet
20 service telephone communication, internet service telephone communication is permitted by guaranteeing the sound quality, i.e., service quality as the service of the VPN of the own subscribed provider.

Other objects and features will be clarified from
25 the following description with reference to attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a construction of an embodiment of the

telephone communication system according to the present invention;

Fig. 2 is a construction of another embodiment of the telephone communication system according to the present invention;

Fig. 3 is a view showing the realization of the telephone set according to the present invention on a personal computer; and

Fig. 4 is a view showing a telephone set according to the present invention, in which an encryption unit is additionally provided.

PREFERRED EMBODIMENTS OF THE INVENTION

Preferred embodiments of the present invention will now be described with reference to the drawings.

An embodiment of the present invention will now be described with reference to Fig. 1. The Figure shows the construction of the embodiment of the telephone communication system according to the present invention.

As shown in Fig. 1, telephone sets 100 and 120 according to the present invention can make telephone communication via a public line and bypass the line for internet service telephone communication in a simple procedure.

The telephone sets 100 and 120 are connected to lines 110 and 140, respectively, which can be interconnected via a public network 150 or an internet service provider network 160. The public network 150 includes LAN, general public network and mobile

communication network.

The telephone sets 100 and 120 comprise ten-key units 101 and 121, display units 102 and 122, telephone set control units 103 and 123, "H323" voice codecs 104 and 124, accumulating units 105 and 125, line interface units 106 and 126 and data modem units 107 and 127, respectively.

The ten-key units 101 and 121 each have keys of numerals "0" to "9" and marks "*" and "#" and other function keys, and can notify telephone number and bypassing and also make other notifications. The display units 102 and 122 each can display call arrival notification and results of processing in the own telephone set. The units 101 and 121 each have a bypassing notification push-button 109 for commanding the start of internet service telephone communication.

003090" 48068550

1934

The telephone set control units 103 and 123 each send out dial data when detecting the depressed push-buttons in each of the ten-key units 101 and 121. When detecting bypassing, the units 103 and 123 each obtain data for bypassing line for internet service from each of the accumulating units 105 and 125, and send out the dial data and connection point data to each of the line interface units 106 and 126. When obtaining caller identifier and subaddress signal from each of the data modem units 107 and 127 upon call arrival, the units 103 and 123 each notify internet telephone call arrival by obtaining the data from each of the accumulating units

invention will now be described. In this embodiment, it is assumed that the telephone set 120 is the transmitting side, and the other telephone set 100 is the receiving side.

5 The calling person on the side of the telephone set 120 makes dialing by operating dial push-buttons in the ten-key unit 121. Specifically, the calling person depresses the bypassing notification push-button 109, and then dials the telephone number of the called side.

10 Detecting the key operation in the ten-key unit 121, the telephone set control unit 123 controls the line interface 126 for sending out the dial number of the called side. Detecting the depression of the bypassing notification push-button 109, the unit 123 retrieves the
15 accumulating unit 125 to call out the telephone number and access identifier as the connection point data to be connected by the called side for internet service telephone communication. The telephone set control unit 123 notifies the called-out connection point data to the
20 line interface unit 126.

 The line interface unit 126 sends out the connection point data notified by the telephone set control unit 123 as subaddress signal obtained by adding the caller identifier to the called side dial number via
25 the data modem unit 127.

 Detecting the call arrival in the line interface unit 106, the telephone set 100 analyzes the caller identifier in the data modem unit 107. The line

interface unit 106 notifies the call arrival and the caller identifier data to the telephone set control unit 103.

5 The telephone set control unit 103 compares the caller identifier received from the line interface unit 106 and the data from the accumulating unit 105 to check whether the numeral figure of a predetermined connection point data format and that of the subaddress signal with the caller identifier are identical. When it is proved
10 as a result of the check that the two numeral figures are identical, the telephone set control unit 103 causes the accumulating unit 105 to preserve the connection point data and also causes the display unit 105 to display the arrival of the internet service telephone
15 communication request. The display unit 102 displays the notification of the arrival of the internet service telephone communication request.

In response to the request arrival notification, the called person depresses an internet service
20 telephone communication start push-button in the ten-key unit 101. Detecting the depression of the internet service telephone communication start push-button in the ten-key unit 101, the telephone set control unit 103 calls out the connection point data, having been sent out from
25 the calling person side, from the accumulating unit 105, and commands transmission to the dial number in the connection point data, thus effecting connection to the access point line.

000000-000000-000000

The telephone set control unit 103 sends out verification of identifier with access point via the data modem unit 107 according to the connection point data. After completion of the verification of identifier with access point, the telephone set control unit 103 starts the "H323" voice codec 104 as internet service voice codec. In this way, the telephone set 100 is connected to the line 110 (i.e., VPN of the internet service provider network 160).

10 In the telephone set 120, the telephone set control
unit 123 detects the connection point data send-out
verification from the line interface unit 126, obtains
preliminarily registered internet service connection
point data of the telephone set 120 from the accumulating
15 unit 127, and dials the connection point via the line
interface unit 126.

The telephone set control unit 123 sends out the verification of identifier with access point via the data modem unit 127 according to the connection point data. After completion of the verification of identifier with access point, the telephone set control unit 123 starts the "H323" codec as internet voice codec, thus connecting the telephone set 120 to the line 140 (i.e., VPN of the internet service provider network 160).

25 The data which are provided in the connection point data, are not limited to the telephone number to be dialed up by the opposite side set and the identifier code at that access point, but the connection point data may also

include other internet service telephone communication data, such as nickname as the internet service telephone set, main address, IP address and gate keeper data.

Where the telephone number or the like is obvious
5 and need not be sent out, such data may be left out. Also,
the caller identifier is by no means limitative as the
data to be added to the connection point data; for example,
it is possible to add ISDN D-channel bucket or
user-to-user data or, in case of "H323" telephone service
10 defined by ITU-T, add as electronic mail or data terminal
file.

Furthermore, the present invention is applicable
not only to the connection to an internet service network
managed by a provider but also to internet service
15 telephone sets in self-managing network WAN or
in-premise AN. The present invention is further
applicable not only to internet service telephone sets
but also meeting telephone sets utilizing an internet
service line or television meeting sets.

20 As has been shown, the telephone sets 100 and 120
according to the present invention can make internet
service telephone communication between them with the
connection of their "H323" codecs 104 and 124 to VPN of
the internet service provider network 160. That is, the
25 telephone set 120 (i.e., the calling side) permits
connection of the telephone set 100 (i.e., the called
side) having no contract regarding VPN subscribed by it
thereto by first connecting itself thereto and then

008090" 48068560

003090-12068560

sending out contract data to the telephone set 100. In this way, the calling and called sides can make mutual internet service telephone communication without contract with any common provider but by utilizing a single provider on a quality-guaranteed internet service line (such as VPN line or Qos guarantee line).

Sub 84
In this way, the present invention permits high speech quality internet service telephone communication. Also, the telephone set according to the present invention can preclude contract expenditure increase due to a plurality of provider contracts effected by a plurality of opposite side telephone sets and burden increase in view of expenditures and operation steps of management and maintenance due to the plurality of contracts.

A different embodiment of the present invention will now be described with reference to Fig. 2. Fig. 2 shows the different embodiment of the telephone set according to the present invention. The preceding embodiment of the telephone set is an internet service telephone set as independent telephone set.

In this embodiment, as shown in Fig. 2, push-button telephone sets 111 and 141 are connected to telephone sets 100 and 120, respectively. The telephone sets 111 and 141 are to be connected via lines 110 and 140, respectively, to a public network 150 and an internet service provider network 160. The telephone sets 111 and 141 are not limited to independent telephone sets or

in-premise switching system terminals; for example, they may be constructed as switching system. Furthermore, the telephone sets 111 and 141 are not limited to analog telephone sets; for example, they may be ITU-T "H323" terminals, ISDN terminals, telephone sets for cable modems and so forth.

Figs. 3 and 4 will now be referred to. Fig. 3 is a view showing the realization of the telephone set according to the present invention on a personal computer. Fig. 4 is a view showing a telephone set according to the present invention, in which an encryption unit is additionally provided.

The telephone set according to the present invention is not limited to an exclusive communication unit. As shown in Fig. 3, it is possible to realize as the telephone set on a personal computer. In Fig. 3, it is shown that it is displayed on a personal computer display screen that connection point data has been received. The user of the personal computer realizes the internet service telephone set with a microphone 171 and a loud-speaker 172 of a PC unit 170 by selecting icon with a mouse and dialing up the designated access point. The icon on the personal computer may be displayed in a browser in a receiving side personal computer, or it may be on a transmitting side web page.

The data on the web may not only be mere dial data of the access point and identifier for verification, but may also be data of ablet type (i.e., execution type)

008090-18058550

such as JAVA ablet accompanied by a telephone call producing operation. Aside from the JAVA ablet, the data may be of execution type via standard API in a data terminal. Files of the execution type via the standard API are not limited to operations in the browser. In execution type on the PC unit 170, it is possible to provide the convenience that the communication is obtainable with the sole click operation of the icon.

In the telephone set shown in Fig. 4, an encyphering unit 108 is provided for sending out the caller identifier and telephone number. With the encyphering unit 180, it is possible that the opposite side of communication or the third party is unable to understand or recognize the sent-out data. It is also possible to prohibit re-uses of the transmission data by encyphering. It is further possible to permit one time right to be maintained until the establishment of communication, so that re-transmission is possible at the time of failure of communication.

In this embodiment, the terminal of internet service telephone communication is constituted by a telephone set and a personal computer. The terminal may also be IVR (Interactive Voice Response unit), facsimile data server, voice recognition dialer or voice mail.

In an embodiment with an IVR, a voice message such as "where to connect?" is given upon reception of a call arrival notification. By giving a command to such a

service provider is utilized, the communication can be made without need of striding between different providers, and thus the service quality (i.e., Qos and packet delay) can be readily guaranteed.

5 Moreover, in the type of execution on personal computer, communication can be made conveniently by merely click operating the icon.

Changes in construction will occur to those skilled in the art and various apparently different modifications and embodiments may be made without departing from the scope of the present invention. The matter set forth in the foregoing description and accompanying drawings is offered by way of illustration only. It is therefore intended that the foregoing description be regarded as
10
15 illustrative rather than limiting.

00589084-060800